



Guanghai Non-slip heat shrink tubing details:

Heat resistant , non-slip , colorful , decorative for fish rod , fitness equipment etc.

Note : Not recommended for implantable or in-body uses or for continuous steam applications.

Product Type	Heat shrink tube
Material	PE
Flame retardant	VW-1
Operation Temperature	-40℃-125℃
Withstand Voltage	600V
Length	Customized
Shrink ratio	2:1
Water absorption	<0.2%
Shrinking temperature	75-125℃
Usage	Low Voltage,Sport equipment, fishing tool etc
Place of Origin	Guangdong, China (Mainland)

General size

Product Parameters

Non-Slip Heat Shrink Tube common specification table

Standard specifics	Inner diameter before shrink(mm)		Inner diameter after shrink(mm)		Standard package (m/piece)
	Inner diameter	Average thickness	Maximum inner diameter	Average thickness	
φ 15.0mm	≥15	0.45±0.15	8		1m/pcs 1.6m/pcs
φ 20.0mm	≥20	0.50±0.15	11		1m/pcs 1.6m/pcs
φ 22.0mm	≥22	0.50±0.15	12.5		1m/pcs 1.6m/pcs
φ 25.0mm	≥25	0.50±0.15	14.5		1m/pcs 1.6m/pcs
φ 28.0mm	≥28	0.50±0.15	15.5		1m/pcs 1.6m/pcs
φ 30.0mm	≥30	0.60±0.15	17.5		1m/pcs 1.6m/pcs
φ 35.0mm	≥35	0.60±0.15	20		1m/pcs 1.6m/pcs
φ 40.0mm	≥40	0.60±0.15	23		1m/pcs 1.6m/pcs
φ 45.0mm	≥45	0.65±0.15	25		1m/pcs 1.6m/pcs
φ 50.0mm	≥50	0.65±0.15	28		1m/pcs 1.6m/pcs

Guanghai Electronic Insulation Materials Co.,Ltd professional in kind of insulation tubes and coated webbing ,
any interested ,please contact us info@gh-material.com

Address : (Plant) 3/F, No. 154, Huasheng East St.,
Chenjiang Street, Zhongkai High-Tech Zone,
Huizhou, Guangdong, China (Mainland)
Tel/Fax: 86-752-3175209
Website: <http://www.gh-material.com>

